TECHNICAL DATASHEET



2588 - BURNED WOOD

Product Description:

2588 Burned Wood represents charred wood without being actually burned. The burned optic is gained by the special embossing process of multiple veneer layers. No unpleasant burnt smell, no dark stains, no crumbling and a closed surface, which does not need to be fixed afterwards.

Composition:

2588 Burned Wood is an embossed panel with special developed veneer and melamine resins with a plywood core

Black Ash optic lacquerd Alpi veneer



Black matte lacquered Alpi veneer

Fields of application:

Only for interior: Interior fittings. Furniture manufacture. Shop and fair construction. Doors.

Technical Data:

First given measurement specifies the direction of embossment:

Invoiced size (mm): 3135 x 1270 Delivered size (mm): 3145 x 1280

Repeating pattern: No repeating pattern

Available thicknesses: 19,5 mm Coreboard: Plywood

Surface: raw, unlacquered

Density: ca. 790 kg/m3 Weight: ca. 14,5 kg/m2

Embossment: one-side
Deepness of structure: max. 1,8 mm

Tolerances:

Straightness: 3,0 mm per Meter
Size accuracy: +/- 1,0 mm per Meter

Thickness allowance: +/- 0,3 mm Exactitude of profile: +/- 1,5 mm

Explanatory notes:

The given details in this data sheet are our field-tested experience. They could not consider any parameter, use case or application and they are therefore without commitment. These data does not represent guarantee of condition in the legal sense or a assurance of the characteristics. No legal claims could be derived by using the information given in these data sheets or by our free of charge technical consultants. Images are for illustration purposes only. Wood is a natural product, deviations in color and texture can occur. Please visit our website for an impression of the color range, which can be expected.

Last update: 10.07.2018